


Thermal Receipt Printer

RETSOL RTP-82UE



USB+LAN Interfaces



- » New sleek shell design
- » Wall mount capable
- » Easy drop-in paper loading
- » Intelligent cutter control system
- » Order comes remind
- » USB + LAN Interfaces



Technical Specification

Model	RTP-82UE	
Printing method	Direct thermal	
Paper width	58±0.5mm / 79.5±0.5mm	
Print width	72mm / 76mm / 80mm / 64mm / 48mm / 52mm	
Column capacity	576 dots / line (adjustable by command)	
Printing Speed	230 mm/s	
Line Spacing	3.75mm (Adjustable by commands)	
Interface	USB + LAN	
Auto cutter	Partial	
Physical Characteristics		
Weight	0.97 Kg	
Dimensions	D 180 x W 140 x H 134.1mm	
Power		
Power adaptor	Input: AC 100-240V / 50~60Hz; Output: DC 24V / 2.5A	
Printer input	DC 24V / 2.5A	
Cash drawer	DC 24V / 1A	
Environmental Requirements		
Operational environment	Temperature (0 ~ 45°C) Humidity (10 ~ 80%)	
Storage environment	Temperature (-10 ~ 60°C) Humidity (10 ~ 90%)	
Reliability		
Cutter life	1.5 million cuts	
Printer head life	150Km	
Software		
Emulation	ESC/POS	
Driver	Windows / JPOS / OPOS / Linux / Android / Mac	
Utility	Windows & Linux test Utility	
SDK	IOS / Android / Windows	
Warranty		
Warranty	One year factory warranty*	

* Warranty - Against Manufacturing Defects on the Printer Specifications are subject to change without notice

