



BP-03L

Portable Bluetooth Receipt Printer

- Compact, Durable performance
- Quick charge with Rechargeable Li-ion Battery
- Dual Connectivity for fast and easy data transfer
- Thermal Label/Receipt Printer



Specification

Print Method	Direct Thermal
Media Width	80 mm (max)
Printing Width	72 mm
Resolution	203dpi (8 dot/mm)
Printing Speed	90 mm/s (max)
Dot/Line	576 dots/line
Print Font	Support most language English/Tamil/Chinese. Supports user-defined fonts and graphics Resident fixed and scalable fonts
Media Roll Size (OD)	50mm
Media Type	Direct thermal/Continuous/Mark /Gap media/Sensor/Paper receipt/Label
Paper feeding method	Easy paper loading
Barcode type (1D/2D)	CODE39/CODE11/CODE93/CODE128, EAN-13/EAN-8/EAN 2/CODABAR/ITF /QR/SBT-128/UPC-A/ UPC-E/PDF417/MicroPDF417/MaxiCode/GS1/ DataBar™ (RSS) family/ Aztec/MSI/ Plessey
Drivers	Windows / OEM certified driver
Interface	Bluetooth BT4.1& BLE (Mfi) /WiFi/USB 2.0 (windows/Android/iOS/ Linux)/RS232
Bluetooth Pairing	Yes
Print out alarm	Battery needs to be charged or changed when battery light turns off and the red light turns on/Support
Printing Command	ESC/POS
Battery	7.4 V 2700 mAh li-ion Battery
Power Supply	USB/Power adapter/Mobile power charging
Dimension (LxWxH)	Length 140mm * width 117mm * height: 60mm/ Weight 450 g
Drop Specification	5ft drop
IP Rating	IP54-compatible
Belt Strap	Available
Operating Temperatures	Working temperature: -10 ^o ~ 50 ^o