



PS-3216A

A Robust, Economical Choice

Featuring a 15.6" wide P-CAP touch screen, the PS-3216A is an Android 9.0 fanless POS Terminal with all the essential functions and capabilities to satisfy businesses of all sizes, and represent one of the best value choices in the entry-level POS Terminal segment.



PS-3216A

Specification	PS-3216A
Processor	Rockchip RK3399, Dual-core Cortex A72 up to 1.8GHz + Quad-core Cortex A53 up to 1.4GHz
System Memory	DDR4 4 GB
Storage Device	32 GB eMMC + microSD slot x 1
Power Supply	12V/40W
OS Support	Android 9.0*/Android 10.0 with GMS
Display & Touch	
LCD	15.6" TFT LCD
Resolution	1366 x 768
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)
I/O & Expansion	
Serial Port	DB9 x 2
Parallel Port	N/A
Standard USB Port	USB 2.0 x 5
PoweredUSB Port	N/A
OTG USB	Micro-USB x 1
LAN Port	10/100/1000 Mb x 1
Display Port	HDMI x 1
CR Port	1, control 2 x cash drawer, 24V support only
PS/2 Port	N/A
Audio	Internal 2W speaker x 1
Expansion Slot	Mini-PCle for WiFi/BT module x 1
Physical Dimension	
Dimension (W x D x H in mm)	372 x 252 x 291.4
Weight (N. W. in kg)	4.7
Environmental	
Operating Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	-20°C - 70°C, 10%RH - 90%RH
Built-in Options	
WiFi	Mini-PCle WiFi/BT module
Attachment Options	
POS Monitor	Non-touch TFT USB LCD: 10.1"; PCAP touch TFT USB LCD: 10.1"
Line Display	2 x 20 rear-mount VFD customer line display; 2 x 20 rear-mount LCD customer line display
Attachment	MSR; iButton; RFID; Fingerprint Sensor; Keypad

















No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan Fax: +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller



^{*}Google Play services is not supported by this device.

^{*}Designed and Manufactured in Taiwan by Posiflex Technology, Inc.
*The product information and specifications are subject to change without prior notice.

^{*}Please refer to the website for more attachment options.