


BS-C 101 STAR | SCANNERS HANDHELD

Advanced high speed CCD scanner



Enabled with ultra scan -
Decoding technology



Express speed - With 330 scans per second, ensures quicker checkouts, serves more customers



Aim & shoot trigger - Gives operational comfort and reduces fatigue especially during peak hours



Durable and strong design - Designed to withstand multiple drops from a height of 5 feet



Plug & play - Easy to install

The BS-C 101 Star Advantage

TVS Electronics BS-C 101 Star is a high speed CCD scanner. It has a scan rate of 330 scans per second, which is the highest among its competitors. Empowered with Ultra Scan decoding technology it can decode a majority of 1D barcodes as well as GS1 Data Bar.

It supports auto scan mode and with an optional stand can work as a hands free scanner. It has a 32 bit microprocessor, which guarantees an unbeatable scan rate and decoding accuracy. The BS-C 101 Star is suitable for a wide range of applications, from retail checkout and inventory management, to invoicing in offices and shipping receiving control in factories.

Number of Pixels - It has 2500 pixels which increases the resolution of the scanner and helps in better decoding of barcodes.

High Scan Rate - The scan speed of 330 scans per second is highest in this category of scanners making it the fastest in its class.

High Depth of Field - Depth of field of up to 300 mm enables decoding from larger distances.

Lower PCS (Print Contrast Signal) - Lower PCS pixels decodes faded barcodes.

Auto Sense / Hands Free - It is enabled with auto sense technology making it convenient to use in hands free mode.

Rugged Body - Able to withstand drops of up to 1.5 m.

Specifications

Operational

Light Source	: 617 nm visible LED
Optical System	: Linear CCD array
Image Catch	: Analog
Microprocessor	: 32 bit
Depth of Field	: 0-300 mm (UPC/EAN 100%, PCS=90%)
Scan Angle	: 42°
Scan Rate	: 330 scans per second
Minimum Bar Width	: 0.1 mm (4 mil) (Code 39, PCS=90%) More than 100 mm on 0.125 mm barcode

Print Contrast	: Min. 30% @ UPC/ EAN 100%
Indicators (LED)	: Blue LED
Beeper Operation	: Programmable tone & beep time
System Interfaces	: Keyboard, RS-232C, HID USB, USB virtual COM port, Wand

Physical Dimensions

Size (L x W x H) mm	: 152.3 x 64.4 x 104.9 mm (device only)
Weight	: 120 g (device only)
Cable	: Field replaceable, Standard 2.0 M straight

Power

Input Voltage	: 5V DC ±5%
Operating Current	: 100 mA typical

Regulatory

EMC	: CE & FCC DOC compliance, VCCI, BSMI
-----	---------------------------------------

Environmental - Operating Conditions

Operating Temperature	: 0°C - 50°C (32°F - 122°F)
Storage Temperature	: -20°C - 60°C (-4°F - 140°F)
Humidity	: 5% - 95% RH (non-condensing)
Ambient Light Immunity	: 0 - 10,000 Lux
Drop Durability	: Designed to withstand 1.5 M drops

Decoding Capability

Barcodes	: Code 39, Code 39 Full ASCII, Code 32, Code 128, UCC/EAN-128, Codabar, Code 11, Code 93, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, China Postal Code, IATA, UPC/EAN/JAN, UPC/EAN/JAN with Addendum, Telepen, MSI/Plessey, GS1DataBar (RSS) Linear, Linear-stacked
Warranty	: 1 year

CUSTOMER SEGMENTS



Retailers



Lotteries



Jewellery Shops



Courier Companies

TVS ELECTRONICS LIMITED:

South Phase 7A, Second Floor,
Industrial Estate, Guindy, Chennai - 600 032.

Call: 1800 200 5123 / 3030 9797 / 3030 7171 (prefix city STD code)

Visit: www.tvse.in

ORDERING INFORMATION

3006220011 BS-C 101 STAR

OPTIONAL ACCESSORIES

2017140022	PS2 CABLE
2017140009	SERIAL CABLE
2017140021	SERIAL ADAPTER

DEALER STAMP